



MAXBRIC™

Maximum Value. Maximum Performance.


4" UTILITY SIZE - CORED
UNIT WT: 10.0 LBS.




4" UTILITY SIZE - SOLID
UNIT WT: 11.4 LBS.




4" REGULAR - CORE PATTERN 1
UNIT WT: 11.8 LBS.




4" REGULAR - CORE PATTERN 2
UNIT WT: 11.8 LBS.




4" REGULAR - CORE PATTERN 3
UNIT WT: 11.2 LBS.




4" REGULAR - SOLID
UNIT WT: 13.0 LBS.




8" CORNER / SASH
UNIT WT: 16.25 LBS.




10" CORNER / SASH
UNIT WT: 22.8 LBS.




12" CORNER / SASH
UNIT WT: 25.5 LBS.




8" HALF UNIT/SASH
UNIT WT: 10.4 LBS.




12" HALF UNIT/SASH
UNIT WT: 13.0 LBS.




8" RESTRICTED BOTTOM BOND BEAM
UNIT WT: 16.25 LBS.




12" RESTRICTED BOTTOM BOND BEAM
UNIT WT: 22.5 LBS.




8" PILASTER
UNIT WT: 16.25 LBS.




10" PILASTER
UNIT WT: 22.8 LBS.




12" PILASTER
UNIT WT: 25.5 LBS.



8" STRETCHER
UNIT WT: 16.25 LBS.




12" STRETCHER
UNIT WT: 25.5 LBS.




MAXBLOC™

Maximum Value. Maximum Performance.


4" REGULAR UNIT WT: 24.0 LBS.




8" PILASTER UNIT WT: 32.25 LBS.




10" PILASTER UNIT WT: 43.0 LBS.




6" STRETCHER UNIT WT: 29.0 LBS.




8" STRETCHER UNIT WT: 36.25 LBS.




10" STRETCHER UNIT WT: 39.5 LBS.




12" STRETCHER UNIT WT: 43.0 LBS.




6" CORNER / SASH UNIT WT: 29.0 LBS.




8" CORNER / SASH UNIT WT: 36.25 LBS.




10" CORNER / SASH UNIT WT: 39.5 LBS.




12" CORNER / SASH UNIT WT: 43.0 LBS.




8" HALF UNIT/SASH UNIT WT: 18.5 LBS.




12" HALF UNIT/SASH UNIT WT: 25.4 LBS.




8" RESTRICTED BOTTOM BOND BEAM UNIT WT: 36.25 LBS.




12" RESTRICTED BOTTOM BOND BEAM UNIT WT: 50.0 LBS.



6" SOLID BOND BEAM UNIT WT: 32.25 LBS.



8" SOLID BOND BEAM UNIT WT: 43.5 LBS.



12" SOLID BOND BEAM UNIT WT: 60.5 LBS.

